

# 7619 Rollout Runway



Rollout Runway 7619 is a prefabricated, resilient, recycled rubber pad engineered to provide temporary protection from running track surfaces. Roll it out over an existing runway or track surface to protect the surface from cleats, spikes, motorized vehicles, and foot traffic. Re-roll it for easy storage. Rollout Runway 7619 is a quick and effective way to protect your athletic surface.

Rollout Runway 7619 can be loose laid over asphalt, concrete, all-weather tracks and indoor hard surfaces for a temporary runway or protective hard surface. Rolls are factory-cut to job specified lengths to reduce scrap and minimize installation handling and time. Seams are to be butt-joined along all joints.

## Physical Data Test

Property	Test Method	Typical Results								
Density	ASTM D297	50 lbs/ft <sup>2</sup>								
Tensile Strength	ASTM D412, Die C	116 psi min								
Elongation	ASTM D412, Die C	74% min								
Tear Strength	ASTM D624, Die C	30 ppi								
Compression/Recovery	F36	<table border="1"> <thead> <tr> <th>Compression</th> <th>Recovery</th> </tr> </thead> <tbody> <tr> <td>@50PSI</td> <td>15% / 81%</td> </tr> <tr> <td>@100PSI</td> <td>28% / 92%</td> </tr> <tr> <td>@200PSI</td> <td>45% / 95%</td> </tr> </tbody> </table>	Compression	Recovery	@50PSI	15% / 81%	@100PSI	28% / 92%	@200PSI	45% / 95%
Compression	Recovery									
@50PSI	15% / 81%									
@100PSI	28% / 92%									
@200PSI	45% / 95%									
Flexibility	F147	0-1 Factor								
Compression Set B	D395	26% Max								
25% deflection, 22 hrs. @ 158° F										
Compression Set (Foam)	D3676	19% Max								
50% deflection, 22 hrs. @ 158° F										
Temperature Stability		-40° to +115°C (-40° to +240° F)								
Post Consumer Recycled Content	F147	93%								

The values shown represent current production and may vary under different conditions.

## Available In

Thickness	Width	Weight
10mm	36", 48"	4.9 lbs/LF, 6.5lbs/LF
12mm	36", 48"	5.9 lbs/LF, 7.9lbs/LF
19mm	48"	12.5 lbs/LF

## Warranty

All Rollout Runway 7619 is guaranteed by Ecore to be free from manufacturing defects on both material and workmanship. If such a defect is discovered, the customer must notify Ecore either through the contracting installer, distributor, or directly. If found to be defective within three years under normal non-abusive conditions, the sole remedy against the seller will be the replacement or repair of the defective goods; or, at the seller's option, credit may be issued not exceeding the selling price of the defective goods.

## Please Note

Rollout runway is not intended to be used as a permanent finished floor. Rollout Runway is treated as a temporary surface covering. Ecore is committed to sustainable manufacturing practices and the reuse of manufacturing products whenever possible to eliminate our waste stream. Because Rollout Runway is not intended as permanent flooring, but a protective cover, Ecore reutilizes first quality manufacturing excess as part of the formula for this product. This may result in visual irregularities, but does not effect the performance of the material.